

725 Multifunction Process Calibrator

Simply powerful



The new Fluke 725 Multifunction Calibrator is a versatile, easy-to-use field calibrator. Use the measure and source functions to test and calibrate almost anything.

- New smaller, streamlined shape makes it easy to carry
- Rugged, reliable design stands up to field use
- Easy to read measure/source screen lets you view input and output simultaneously
- Measure volts, mA, RTDs, thermocouples, frequency, and ohms to test sensors and transmitters
- Source/simulate volts, mA, thermocouples, RTDs, frequency, ohms, and pressure to calibrate transmitters
- Measure/source pressure using any of 29 Fluke 700Pxx Pressure Modules
- Source mA with simultaneous pressure measurement to conduct valve and I/P tests
- Support flow meter testing with frequency and CPM (counts per minute) functions
- Perform fast linearity tests with auto step and auto ramp features
- Power transmitters during test using loop supply with simultaneous mA measurement
- Store frequently-used test setups for later use
- Backlight lets you work in poor light
- Remote interface allows benchtop automated operations
- Large battery capacity of four AA cells
- Battery door for easy changes

Simultaneous Function Capability	Channel A	Channel B
24.000 mA DC	M	M or S
24.000 mA DC with 24V loop supply	M	
100.00 mV DC		M or S
30.000V DC Measure	M	
20.000V DC Measure 10.000V DC Source		M or S
15 to 3200 Ohms		M or S
Thermocouple J, K, T, E, R, S, B, L, U, N		M or S
RTD Ni120; Pt100 (392); Pt100 (JIS); Pt100, 200, 500, 1000 (385)		M or S
Pressure Eleven Engineering Units; use Fluke 700PXX Modules	M	M used as S
Frequency; Squarewave, 1 CPM to 10 kHz; fixed amplitude 5V p-p		M or S

M = Measure S = Source/Simulate

Specifications

Summary specifications (18°C to 28°C for one year)

Function	Range	Resolution	Accuracy	Notes
Measure or Source Voltage	0 to 100 mV	0.01 mV	0.02% Rdg + 2 LSD	Max load, 1 mA
	0 to 10V (source) 0 to 30V (measure)	0.001V 0.001V		
mA	0 to 24	0.001 mA	0.02% Rdg + 2 LSD	Max load, 1000Ω
mV	-10.00 mV to +75.00 mV	0.01 mV	0.025% + of range + 1 LSD	
Resistance	0Ω to 3200Ω (measure)	0.01Ω to 0.1Ω	0.10Ω to 1.0Ω	
	15Ω to 3200Ω (source)			
Frequency	1 CPM to 10 kHz	5 digits	0.05% + 1 count	Squarewave
Loop Supply	24V DC	N/A	10%	
Thermocouples	J,K,T,E,L,N,U	0.1°C	to 0.7°C	
Thermocouples	B,R,S	1°C	to 1.4°C	
RTDs	Ni120 (672)	0.1°C	to 0.2°C	
	Pt 100, 200, 500, 1000 (385)			
	Pt 100 (3916)			
	Pt 100 (3926)			

Maximum voltage: 30V

Storage temperature: -20°C to 71°C

Operating temperature: -10°C to 55°C

Relative humidity: 90% (10°C to 35°C); 75% (30°C to 40°C); 45% (40°C to 50°C); 35% (50°C to 55°C)

Shock: 30g, 11ms, half-sine shock (or 1meter drop test)

Vibration: Random, 2g, 5-500 Hz

Safety: CSA C22.2 No. 1010.1:1992

EMC: EN50082-1:1992 and EN55022:1994 Class B

Size/weight (HxWxD): 96 x 200 x 47 mm ; 0.65 kg

Battery: Four AA alkaline batteries. Battery life: 25 hours typical

Three Year Warranty

Accessories and Ordering Information

Included Accessories

Each calibrator includes TL75 Test Leads, AC70A Test Clips, one pair of stackable test leads, user's Manuals.

Ordering Information

Fluke 725 Multifunction Process Calibrator